

CHAMBER VOL	63.3	0	0	0	0
CYL DIAMETER	4.04	0	0	0	0
STROKE	3.5	0	0	0	0
GASKET BORE DIA	4.06	0	0	0	0
GASKET THICKNESS	0.04	0	0	0	0
PISTON DOME VOL	0	0	0	0	0
PISTON DISH VOL	5.26	0	0	0	0
PISTON TO DECK HT	0.015	0	0	0	0
NUMBER OF CYL'S	8	0	0	0	0
CID	358.932	0	0	0	0
COMP RATIO	10.1678	ERR	ERR	ERR	ERR

PART # 32-225-4  
 ENGINE FORD 351C - 400M

GRIND NUMBER FC 280H-10  
 MAGNUM CAM

VALVE ADJUSTMENT	INTAKE	EXHAUST
GROSS VALVE LIFT	HYD	HYD
DURATION AT .006	.530	.530
TAPPET LIFT	280	280

VALVE TIMING	OPEN	CLOSE
AT .006 INT	34 BTDC	66 ABDC
EXH	74 BBDC	26 ATDC

THESE SPECS ARE FOR CAM INSTALLED  
 AT 106 INTAKE CENTER LINE

DURATION AT .050	INTAKE	EXHAUST
LOBE LIFT	230	230
LOBE SEPARATION	.3063	.3063
	110	

RECOMMENDED CC VALVE SPRG 972  
 VALVE SPRING SPECS FURNISHED  
 WITH SPRINGS